



display
lighting ltd

design & manufacture of specialist lighting for retail & exhibition displays...

displayLED

APPLICATIONS:

- Showcases
- Window Displays
- Museums
- Exhibitions

COOL WHITE LED - 10000k

- ✓ Diamonds
- ✓ Watches
- ✓ Silver
- ✓ China
- ✓ Crystal

NEUTRAL WHITE LED – 4000k

- ✓ Diamonds
- ✓ Watches
- ✓ Silver
- ✓ China
- ✓ Crystal
- ✓ Gold
- ✓ Brass
- ✓ Copper

WARM WHITE LED - 3500k

- ✓ Gold
- ✓ Brass
- ✓ Copper



- ✓ Very Low Heat.
- ✓ No UV.
- ✓ No Infra Red.
- ✓ Uniform Intensity.
- ✓ Very Long Life.
(50'000 Hours typical)
- ✓ Only 15mm Diameter.

- ✓ Very slim circular aluminium profile (Diameter 15mm).
- ✓ Built in very high density SMD LED strip for uniform illumination.
- ✓ 120 high bright LED's (19.2W) per metre.
- ✓ Each LED outputs 4000mcd.
- ✓ Easy clean dustproof acrylic diffuser.
- ✓ Shelf support system with easy to adjust shelf holders.
- ✓ Operates from 12V or 24V DC power supply.
- ✓ Typical life of over 50'000 hours.
- ✓ cool white, neutral white or warm white LED's.
- ✓ 60 degree beam angle.
- ✓ Available in lengths up to 2000mm.
- ✓ Fixings available for vertical or horizontal mounting.
- ✓ High quality polished finish.
- ✓ CE & RoHS compliant.
- ✓ Available as part of the Carbon Trust Interest Free Loan Scheme.

The integral 3528 flexible LED strip offers a high intensity uniform illumination, particularly suited to illuminating showcase displays, i.e. jewellery, watches, ceramics etc.



displayLED (DLED)



- Wattage. **19W per Metre**
- Current. **12V DC**
- Beam Angle. **60 Degrees**
- LED Colours. **Warm White (WW)**
- . **Neutral White (NW)**
- . **Cool White (CW)**
- Diameter. **15mm**
- Length. **100mm to 2000mm**
- Rotation. **350° with all fixing types.**
- Connection. **Parallel**



display
lighting ltd

design & manufacture of specialist lighting for retail & exhibition displays...

displayLED - Face Fix Base (FF15)




Diameter – **31mm**
Height – **15mm**
Fixing – **Screw Fix**
Cut-out – **Ø7mm**
Material – **Brass**
Finish - **Chrome**

displayLED - Rear Fix Base (RF15)



Diameter – **21mm**
Height – **15mm**
Fixing – **Thread**
Cut-out – **Ø14mm**
Material – **Brass**
Finish - **Chrome**

displayLED - Surface Fix Base (SF15)



Diameter – **22mm**
Overall Height – **28.50mm**
Height to Centre – **18mm**
Fixing – **Screw Fix**
Cut-out – **N/A**
Material – **Brass**
Finish - **Chrome**

displayLED – Shelf Holder (SH15)



Diameter – **22mm**
Overall Length – **36mm**
Length to Centre – **26mm**
Fixing – **N/A**
Cut-out – **N/A**
Material – **Brass**
Finish - **Chrome**

displayLED – Mounting Clips (MC15.03)



Diameter – **16mm**
Width – **8mm**
Height to Centre – **10mm**
Fixing – **Screw Fixing**
Cut-out – **N/A**
Material – **Spring Steel**
Finish – **Bright Zinc Plate (BZP)**

Spectrum LED Pro Spotlights – (S142)



Wattage. **3W**
Current. **700mA**
Beam Angle. **15, 25, 45 or 60 Degrees**
LED Colours. **Warm White (WW)**
Cool White (CW)
Diameter. **25mm**
Adjustment. **90°**
Rotation. **350°**
Connection. **Series**

t. 0161 929 3355 f. 0161 929 3356 e. sales@display-lighting.com