

DATA SHEET

CSVL2 | CSTL2



Specialist Counter & Showcase Lighting Systems

CSVL2 Technical Specification



Head Diameter: Ø25.40mm

Wattage: 2 x 1.5W

Input Voltage: 350mA Constant Current

Beam Angle: 45°

Lumens @350mA: 2 x 120lm

Finishes: See Ordering below

Colour Temperature/s: See Ordering below

Tube Diameter: Ø6.55mm

Mount: Vertical

Material: Brass/Aluminium

Rotation: 350°

Fixing: See Fixings below

Adjustment: 90°

Life Expectancy: 30'000 Hours *

Lamp: Integral LED (Not Replaceable)

DATA SHEET

CSTL2 Technical Specification



Overall Height:	< 500mm
Head Diameter:	Ø25.40mm
Wattage:	2 x 1.5W
Input Voltage:	350mA Constant Current
Beam Angle:	45°
Lumens @350mA:	2 x 120lm
Finishes:	See Ordering below
Colour Temperature/s:	See Ordering below
Tube Diameter:	Ø6.55mm
Mount:	Vertical
Material:	Brass/Aluminium
Rotation:	350°
Fixing:	See Fixings below
Adjustment:	90°
Life Expectancy:	30'000 Hours *
Lamp:	Integral LED (Not Replaceable)

In Series Connectors



DL111850 3 Way (2 Bridges)



DL111860 6 Way (3 Bridges)



DL111861 1m Extension



DL111862 2m Extension



DL111863 Spare Bridges (5)

Tubelight MULTI LED

Quality retail showcase lighting systems




DATA SHEET

Recommended LED Drivers		<i>Luminaires are not guaranteed unless operated with LED driver supplied by Display Lighting Ltd</i>			
Model Number	Input Voltage	Output Current	Wattage	Dimming	
PCC35009TD	220V – 240V	350mA (6 – 26V)	9W	Triac	
PCC35012	220V – 240V	350mA (2 – 34V)	12W	No	
PCC35012TD	220V – 240V	350mA (12 – 35V)	12W	Triac	
PCC35018	220V – 240V	350mA (6 – 52V)	18W	No	
PCC35018TD	220V – 240V	350mA (15 – 52V)	18W	Triac	
PCC35020	220V – 240V	350mA (2 – 58V)	20W	No	
L05011i2	180V – 240V	150-1200mA (6 – 42V)	20W	1 – 10V	
CV25	180V – 277V	350mA (6 – 54V)	25W	1 – 10V	
CV40	180V – 295V	350mA (2 – 100V)	40W	1 – 10V	

Constant Current power supplies must be wired in series in accordance with data sheet accompanying the product

Fixings:

RF10 Rear Fix (M10 Nut & Washer)



Diameter: **Ø22mm**

Height: **25mm**


Fixing: **M10 x 50mm Thread** (other lengths available)

Cutout: **Ø11mm**

Material: **Brass**

Mounting: **Vertical / Horizontal**

FF10 Face Fix (Hidden Fixing Bezel)



Diameter: **Ø30mm**

Height: **25mm**

Fixing: **Screw Fix**

Cutout: **Ø7mm**

Material: **Brass**

Mounting: **Vertical / Horizontal**

Ordering

Type / No of Spotlights	Spotlight	Colour Temperature	Overall Height	Fixing	Finish
CSV L2	S152	CW (5000K CRI80>)	100mm - 500mm	RF10	01 White
CST L2		NW (4000K CRI80>)		FF10	03 Black
		WW (3000K CRI90>)			03 Chrome
					05 Brushed Chrome

Example Code: **CSV L2.S152.CW.200.FF10.03**

Tubelight Multi LED luminaires are manufactured and supplied with 1m flying leads as standard.