

PRODUCT INFORMATION

CSV2 | CST2 Single Fix LED Display Spotlights



Tubelight Multi LV has been designed specifically to illuminate Retail & Museum counters and is manufactured to exact height to fit exactly into new furniture or retrofit into existing displays. The spotlights are independently adjustable and can rotate through 350 degrees and tilt through 90°, there are a number of different fixings available to make installation as quick and easy as possible. Tubelight Multi LV can be supplied with the spotlights facing at 180° to each other (CST2) or spaced at 90° (CSV2) for fixing into the corners of counters.

Tubelight Multi LV spotlights by Display Lighting Ltd are designed to accept MR11 & MR16 LED retrofit lamps. The spotlights are constructed from brass to ensure consistent high quality powder coated and electroplated finishes. There are different PLUG & disPLAY power supply options available to operate a single spotlight or power share and operate a number of spotlights from a single power supply.

- **MR11 or MR16 LED lamps.**
- **Dimmable** (*check lamp compatibility*).
- **Various beam angles available.**
- **Low heat illumination.**
- **No ultraviolet light so does not fade materials.**
- **Uniform shadow-free illumination.**
- **Unobtrusive.**
- **Bespoke product manufactured to specific overall height.**
- **Reduces heat emissions and heat build-up in case.**
- **Reduces energy bills by up to 80% compared to traditional light sources.**

Tubelight Multi LV

Quality retail showcase lighting systems



DATA SHEET

CSV2 Spotlight Specification:



Model shown: **CSV2.S112.250.FF10.03**

Overall Height:	100mm to 1075mm (to specification)	
Head Diameter:	Ø25mm	
Watts:	See lamp data	
Input Voltage:	12V DC	
Finishes:	See ordering below	
Tube Diameter:	Ø9.50mm	
Mount:	Vertical	Horizontal
Material:	Brass/Steel	
Spotlight rotation:	350°	
Fixings:	See Fixings below	
Adjustment/Tilt:	90°	
Lamp:	S112 (MR11 GU4)	S122 (MR16 GU5.3)
Spotlight Spacing:	90°	

CST2 Spotlight Specification:




Display
Lighting recommends glass
COB LED Retrofit Lamps

Model shown: **CST2.S122.250.FF10.03**

Overall Height:	100mm to 1075mm (to specification)	
Head Diameter:	Ø25mm	
Watts:	See lamp data	
Input Voltage:	12V DC	
Finishes:	See ordering below	
Tube Diameter:	Ø9.50mm	
Mount:	Vertical	Horizontal
Material:	Brass/Steel	
Spotlight rotation:	350°	
Fixings:	See Fixings below	
Adjustment/Tilt:	90°	
Lamp:	S112 (MR11 GU4)	S122 (MR16 GU5.3)
Spotlight Spacing:	180°	

Fixings:

RF10 Rear Fix (Nut & Washer)




Diameter:	Ø22mm
Height:	25mm
Fixing:	M10 x 50mm Thread (other lengths available)
Cutout:	Ø11mm
Material:	Brass
Mounting:	Vertical / Horizontal

DATA SHEET

Fixings (continued):

FF10 Face Fix (Nut & Washer)



Diameter: **Ø30mm**

Height: **25mm**

Fixing: **M10 x 50mm Thread** (other lengths available)

Cutout: **Ø7mm**

Material: **Brass**

Mounting: **Vertical / Horizontal**

Power Supplies:

12V DC LED Drivers

Model Number	Input Voltage	Output Voltage	Wattage	Dimming
PCV1212	220 - 240V	12V DC	12W	N/A
PCV1220	220 - 240V	12V DC	20W	N/A
PCV1236	100 - 240V	12V DC	36W	N/A
PCV1260	100 - 240V	12V DC	60W	N/A

Constant Voltage power supplies can be supplied complete with 2m Mains Lead with UK or Euro Plug if requested

Type	Spotlight	Overall Height	Fixing	Finish
CSV2	S112 (MR11)	100 to 1075mm	RF10	01 White
CST2	S122 (MR16)		FF10	02 Black
				03 Chrome
				04 Brass
				05 Brushed Chrome
				06 Antique Brass
				07 Polished Nickel
				09 Silver
				XXX RAL Colour

Example code: **CSV2.S112.300.FF10.03**

All Tubelight Multi LV luminaires are manufactured and supplied with 1m flying leads as standard, other lengths are available to order.

 display lighting
Illuminating displays, increasing sales