

DPSLED Premium Gantry Surround Luminaires



DPSLED Premium Gantry Luminaires

have been designed to be integrated into glass display cases and counters to give a uniform high output illumination eradicating inherent shadows and making your displays sparkle.


The circular horizontal LED profile produces a powerful even wash of light and is available with four different colour temperatures (CCT) all with high colour rendering (CRI90>) to ensure your products are illuminated to their full potential.

- Integrated high density LEDs (140/m).
- Adds 'sparkle' to jewellery, watches and glass.
- Low heat illumination.
- No ultraviolet light so does not fade materials.
- Uniform shadow-free illumination.
- Unobtrusive.
- Bespoke/Made to measure product.
- Reduces heat emissions and heat build-up in store.
- Reduces energy bills by up to 80%.

Technical Specifications

Length:	<1500mm (measured to fixing centres)
Width:	<1500mm (measured to fixing centres)
Height:	<1000mm (visible height)
Material/s:	Aluminium/Brass
Electrical Connection:	Plug & Play Hard Wired (1000mm tails as standard, can be specified)
CCT (Lumens per Metre):	WW - 3000K (1540lm/m) NW - 4000K (1680lm/m) CW - 5700K (1820lm/m) CN - 3000K/5700K (1680lm/m)
Watts per Metre:	15W
Fixings:	5 fixing options available (see page 2)
CRI Rating:	CRI90>
Class:	III
IP Rating:	IP20
Adjustment:	LED profile can be rotated and fixed in position
Finishes:	01 - White 02 - Black 03 - Chrome 04 - Gold 05 - Brushed Chrome XXX - RAL Colours
LEDs per Metre:	140 (high density)
Horizontal LED Profile Diameter:	15mm
Tube Support Diameter:	6.50mm
Input Voltage:	24VDC (constant voltage)
Beam Angle:	60 Degrees
Warranty:	5 Years
Dimming:	ON/OFF 1-10V TRIAC DALI DMX Bluetooth (Casambi)
Diffusers:	W - White (50% Opacity) O - Opal (20% Opacity) C - Clear
Ordering:	8 step order code (see page 3)

DPLED Premium Gantry Luminaires



RF Rear Fixing

Diameter: 20mm


Height: 25mm

Fixing: M10 x 50mm Metric Fine Thread with Nut & Washer

Cutout Diameter: 11mm

Material: Brass

Mounting: Vertical or Horizontal



FF Face Fixing (*Hidden Bezel*)

Diameter: 30mm


Height: 25mm

Fixing: Screw Fix

Cutout Diameter: 7mm

Material: Brass

Mounting: Vertical or Horizontal



RFS Small Rear Fixing

Diameter: 20mm


Height: 25mm

Fixing: M8 x 20mm Metric Fine Thread with Nut & Washer

Cutout Diameter: 9mm

Material: Brass

Mounting: Vertical or Horizontal



HF Hidden Fixing (*Floating Cover*)

Diameter: 30mm


Height: 25mm

Fixing: Screw Fix

Cutout Diameter: 7mm

Material: Brass

Mounting: Vertical



HFB Hidden Fixing Bezel

Diameter: 27mm

Height: 12mm

Fixing: Screw Fix (*Underside*)

Cutout Diameter: 7mm

Material: Brass

Mounting: Vertical or Horizontal

DPLED Premium Gantry Luminaires

POWER & DIMMING OPTIONS

- P&P** Plug & Play - Standard On/Off Driver (2m mains lead & UK plug)
- P&P/BT:** Plug & Play -  Bluetooth Controllable Driver (no mains lead)
[Casambi App available for IOS on App Store & Android on Google Play Store](#)
- P&P/DA:** Plug & Play - 1-10V Dimmable Driver (no mains lead)
- P&P/DAP:** Plug & Play - 1-10V Dimmable Driver with Pot Dimmer (2m mains lead & UK plug)
- P&P/DD:** Plug & Play -  Dimmable Driver (no mains lead)
- P&P/DT:** Plug & Play - Mains (TRIAC) Dimmable Driver (no mains lead)
- X:** Driver or Dimmer not required (*not recommended*)

EIGHT STEP ORDERING

	1	2	3	4	5	6	7	8
MODEL	LENGTH	WIDTH	CCT	HEIGHT	DIFFUSER	FIXING	FINISH	POWER
DPSLED/24	< 1500mm	< 1500mm	WW NW CW CN	< 1000mm	W O C	RF FF RFS HF HFB	01 02 03 04 05 XXX (RAL)	P&P P&P/BT P&P/DA P&P/DAP P&P/DD P&P/DT X

Example Order Code: **DPSLED/24.1000.500.CW.300.O.FF.02.P&P**

NOTES:

