

SLED 24V Surface Linear Luminaires



SLED 24V Surface Linear Luminaires have been designed to be integrated into display cases and under shelving. Giving a uniform illumination to your displays and eradicating inherent shadows making your displays sparkle.

The surface LED profile produces a powerful even wash of light and is available with many different colour temperatures (CCT) to ensure your products are illuminated to their full potential.

- 120 LEDs/m.
- CRI80>.
- Adds 'sparkle' to jewellery, watches and glass.
- Low heat illumination.
- No ultraviolet light so does not fade materials.
- Uniform shadow-free illumination.
- Unobtrusive.
- Bespoke/Made to measure product.
- Reduces heat emissions and heat build-up in store..

Technical Specifications

Length: <2500mm (measured to fixing centres)

Width: 18mm

Overall Height: 13mm

Material/s: Aluminium/Polycarbonate

Electrical Connection: Plug & Play | Hard Wired (1000mm tails as standard, can be specified)

Watts/m (Lumens per Metre) CCT's :

- 4.8W/m (394lm-480lm/m): 2700K | 3000K | 4000K
- 9.6W/m (787lm-883lm/m): 2700K | 3000K | 4000K | 6500K
- 12W/m (1080lm-1200lm/m): 2700K | 3000K | 4000K | 6500K
- 19.2W/m (1340-1550lm/m): 2700K | 3000K | 4000K | 6500K
- 9.6W/m (360lm-410lm/m): Tuneable White 2700K-6500K
- 19.2W/m (720lm-820lm/m): Tuneable White: 2700K-6500K
- 14.4W/m (506lm/m): RGB
- 28.8W/m (850lm/m): RGB
- 17.8W/m (902lm/m): RGBW (RGB+3000K)
- 24W/m (1440lm/m): RGB CCT (RGB+2700K-6500K)

Fixings: Screw Fix Brackets (DL83374832) or VHB Tape (DL220000)

CRI Rating: CRI80>

Class: III

IP Rating: IP20

Finishes: 01 - White (Powder Coated)

02 - Black (Powder Coated)

11 - Anodised Satin Silver

XXX - RAL Colours (Powder Coated)

LEDs per Metre: 120

Input Voltage: 24VDC

Beam Angle: 120 Degrees

Warranty: 3 Years

Diffusers: W - White (50% Opacity)

O - Opal (20% Opacity)

Ordering: 6 step order code (see page 2)

SLED 24V Surface Linear Luminaires

6 STEP ORDERING

	1	2	3	4	5	6
MODEL	LENGTH	CCT	Watts/m	DIFFUSER	FINISH	POWER
SLED/24	< 2500mm	VWW - 2700K WW - 3000K NW - 4000K DW - 6500K Tuneable RGB RGBW RGCCT	4.8W 9.6W 12W 14.4W 19.2W 17.8W 24W 28.8W	W (White) O (Opal)	01 02 11 XXX (RAL)	P&P P&P/BT P&P/DA P&P/DAP P&P/DD P&P/DT X

Example Order Code: SLED/24.1000.NW.O.11.P&P

NOTES:

