

Spectrum S152 LED Pro Spotlights



Spectrum LED Pro display spotlights from Display Lighting incorporate a single high power LED that is carefully constructed into a high quality, hard wearing and reliable contemporary luminaire.


The design ensures that the spotlights are as unobtrusive as possible so that your products are illuminated to their full potential without obstruction.

- Integrated LED.
- Specialised focused lighting for museum and retail showcases.
- Low heat illumination.
- No ultraviolet light so does not fade materials.
- Unobtrusive.
- Bespoke product manufactured to your specification.
- Reduces heat emissions and heat build-up in store.
- Reduces energy bills by up to 80%.
- Dimmable

Technical Specifications


Head Diameter:	25mm
Height:	< 1000mm (visible height)
Material/s:	Aluminium/Brass
Electrical Connection:	Plug & Play Hard Wired (1000mm tails as standard, can be specified)
CCT (Lumens):	VWW - 2700K (105lm) VW - 3000K (105lm) NW - 4000K (144lm) CW - 5000K (150lm)
Watts:	1W (integrated non-user replaceable LED)
UV:	0.2 microwatts/m2
Fixings:	6 fixing options available (see page 2)
CRI Rating:	CRI90>
Class:	III
IP Rating:	IP20
Rotation Tilt:	350 Degrees 90 Degrees
Finishes:	01 - White 02 - Black 03 - Chrome 04 - Gold 05 - Brushed Chrome 06 - Antique Brass 07 - Polished Nickel 08 - Brushed Nickel 15 - Brushed Brass 16 - Rose Gold XXX - RAL Colours
Tube Support Diameter:	6.50mm
Input Voltage:	350mA (constant current 3.2Vf)
Beam Angles:	10 25 40 Degrees
Warranty:	5 Years
Dimming:	(ON/OFF 1-10V TRIAC DALI DMX Bluetooth (Casambi))
Ordering:	7 step order code (see page 3)

Spectrum LED Pro Spotlights




RF Rear Fixing

- Diameter:** 20mm
Height: 25mm
Fixing: M10 x 50mm Metric Fine Thread with Nut & Washer
Cutout Diameter: 11mm
Material: Brass
Mounting: Vertical or Horizontal




FF Face Fixing (*Hidden Bezel*)

- Diameter:** 30mm
Height: 25mm
Fixing: Screw Fix
Cutout Diameter: 7mm
Material: Brass
Mounting: Vertical or Horizontal




RFS Small Rear Fixing

- Diameter:** 20mm
Height: 25mm
Fixing: M8 x 20mm Metric Fine Thread with Nut & Washer
Cutout Diameter: 9mm
Material: Brass
Mounting: Vertical or Horizontal




HF Hidden Fixing (*Floating Cover*)

- Diameter:** 30mm
Height: 25mm
Fixing: Screw Fix
Cutout Diameter: 7mm
Material: Brass
Mounting: Vertical



HFB Hidden Fixing Bezel

- Diameter:** 27mm
Height: 12mm
Fixing: Screw Fix (*Underside*)
Cutout Diameter: 7mm
Material: Brass
Mounting: Vertical or Horizontal



SM 60 Degree Surface Mount Bracket

- Width:** 25mm
Height: 26mm
Fixing: Screw Fix
Cutout Diameter: N/A
Material: 1.5mm Steel
Mounting: Vertical or Horizontal

Spectrum S152 LED Pro Spotlights

POWER & DIMMING OPTIONS

P&P Plug & Play - Standard On/Off Driver (2m mains lead & UK plug)

P&P/BT: Plug & Play -  Bluetooth Controllable Driver (no mains lead)

[Casambi App available for IOS on App Store & Android on Google Play Store](#)

P&P/DA: Plug & Play - 1-10V Dimmable Driver (no mains lead)

P&P/DAP: Plug & Play - 1-10V Dimmable Driver with Pot Dimmer (2m mains lead & UK plug)

P&P/DD: Plug & Play -  Dimmable Driver (no mains lead)

P&P/DT: Plug & Play - Mains (TRIAC) Dimmable Driver (no mains lead)

X: Driver or Dimmer not required (*not recommended*)

SEVEN STEP ORDERING

	1	2	3	4	5	6	7
MODEL	HEIGHT	CCT	FIXING	BEAM ANGLE	FINISH	PER SET	POWER
S152	< 1000mm	CW NW WW	RF FF RFS HF HFB SM	10 25 40	01 02 03 04 05 06 07 08 15 16 XXX (RAL)	X1 X2 X3 X4 X5 X6 X7 X8 X9 X10	P&P P&P/BT P&P/DA P&P/DAP P&P/DD P&P/DT X

Example Order Code: S152.250.NW.RF.10.15.X2.P&P

NOTES:

