

MagTrack 24VDC LED Magnetic Track Lighting System




MagTrack II is a magnetic track system incorporating fixed or adjustable high CRI (CRI90+) LED magnetic spotlights that is ideal for use in retail or museum displays & furniture. MagTrack II Magnetic Track enables simple adjustment and positioning of the spotlights to suit changing displays and because it is a 24VDC system is completely safe for end users. The track can be fixed horizontally inside display cases or vertically to allow the spotlights to illuminate shelving fixed at different heights. The track can be screw fixed using the pre-drilled holes or fixed to clean smooth surfaces using high bond double sided adhesive tape. MagTrack II is supplied in 1.5m lengths and can be cut to length easily using a hack saw or joined together to form longer lengths using the neodymium magnetic in line connectors. MagTrack II track and accessories are available in black and silver finishes.

DL6813 - MagTrack II Black



Length: **1500mm**
 Width: **18mm**
 Depth: **6mm**
 Input Voltage: **24VDC**
 Material: **Polycarbonate/Steel**
 Finish: **Black**
 Fixing: **Screw Fix or VHB Tape (Supplied)**

DL6830 - MagTrack II Silver



Length: **1500mm**
 Width: **18mm**
 Depth: **6mm**
 Input Voltage: **24VDC**
 Material: **Polycarbonate/Steel**
 Finish: **Silver**
 Fixing: **Screw Fix or VHB Tape (Supplied)**


DL6911 - In Line Connector



Length: **20mm**
 Width: **3mm**
 Depth: **3mm**
 Input Voltage: **24VDC**
 Material: **Neodymium**
 Finish: **Silver**
 Fixing: **Magnetic**


MagTrack 24VDC LED Magnetic Track Lighting System

DL6850 - Power Feed / Live End - Black



Length: **24mm**
 Width: **18mm**
 Depth: **7mm**
 Input Voltage: **24VDC**
 Material: **Polycarbonate/Steel**
 Finish: **Black**
 Lead Length: **2.5m**

DL6867 - Power Feed / Live End - Silver



Length: **24mm**
 Width: **18mm**
 Depth: **7mm**
 Input Voltage: **24VDC**
 Material: **Polycarbonate/Steel**
 Finish: **Silver**
 Lead Length: **2.5m**

DL6881 - 90 Degree Corner Connector - Black



Length: **26mm**
 Width: **26mm**
 Depth: **7mm**
 Input Voltage: **24VDC**
 Material: **Polycarbonate/Steel**
 Finish: **Black**
 Fixing: **Magnetic**

DL6898 - 90 Degree Corner Connector - Silver



Length: **26mm**
 Width: **26mm**
 Depth: **7mm**
 Input Voltage: **24VDC**
 Material: **Polycarbonate/Steel**
 Finish: **Silver**
 Fixing: **Magnetic**

DL6928 - End Cap / Dead End - Black



Length: **2mm**
 Width: **18mm**
 Depth: **7mm**
 Input Voltage: **N/A**
 Material: **Polycarbonate**
 Finish: **Black**
 Fixing: **N/A**

DL6935 - End Cap / Dead End - Silver



Length: **2mm**
 Width: **18mm**
 Depth: **7mm**
 Input Voltage: **N/A**
 Material: **Polycarbonate**
 Finish: **Silver**
 Fixing: **N/A**

MagTrack 24VDC LED Magnetic Track Lighting System

DL5010.NW.10 - 1W Adjustable Spotlight (4000K) Black



Diameter: 22mm
Height: 60mm
Width: 22mm
Input Voltage: 24VDC
Watts | CRI: 1W | CRI90>
Lumens: 60lm
Tilt: 90 Degrees
Rotation: 350 Degrees
Beam Angle: 20 Degrees
Lamp: Non User Replaceable LED
Material: Aluminium/Polycarbonate
Finish: Black Anodised
Fixing: Magnetic

DL5010.NW.11 - 1W Adjustable Spotlight (4000K) Silver



Diameter: 22mm
Height: 60mm
Width: 22mm
Input Voltage: 24VDC
Watts | CRI: 1W | CRI90>
Lumens: 60lm
Tilt: 90 Degrees
Rotation: 350 Degrees
Beam Angle: 20 Degrees
Lamp: Non User Replaceable LED
Material: Aluminium/Polycarbonate
Finish: Silver Anodised
Fixing: Magnetic

DL5011.NW.10 - 2W Adjustable Spotlight (4000K) Black



Diameter: 22mm
Height: 67.8mm
Width: 22mm
Input Voltage: 24VDC
Watts | CRI: 2W | CRI90>
Lumens: 120lm
Tilt: 90 Degrees
Rotation: 350 Degrees
Beam Angle: 20 Degrees
Lamp: Non User Replaceable LED
Material: Aluminium/Polycarbonate
Finish: Black Anodised
Fixing: Magnetic

DL5011.NW.11 - 2W Adjustable Spotlight (4000K) Silver



Diameter: 22mm
Height: 67.8mm
Width: 22mm
Input Voltage: 24VDC
Watts | CRI: 2W | CRI90>
Lumens: 120lm
Tilt: 90 Degrees
Rotation: 350 Degrees
Beam Angle: 20 Degrees
Lamp: Non User Replaceable LED
Material: Aluminium/Polycarbonate
Finish: Silver Anodised
Fixing: Magnetic

MagTrack 24VDC LED Magnetic Track Lighting System

DL6021.NW.10 - 2W Adjustable Spotlight (4000K) Black



Diameter: 22mm
Height: 48.5mm
Width: 22mm
Input Voltage: 24VDC
Watts | CRI: 2W | CRI90>
Lumens: 80lm
Tilt: 40 Degrees
Rotation: 350 Degrees
Beam Angle: 20 Degrees
Lamp: Non User Replaceable LED
Material: Aluminium/Polycarbonate
Finish: Black Anodised
Fixing: Magnetic

DL6021.NW.11 - 2W Adjustable Spotlight (4000K) Silver



Diameter: 22mm
Height: 48.5mm
Width: 22mm
Input Voltage: 24VDC
Watts | CRI: 2W | CRI90>
Lumens: 80lm
Tilt: 40 Degrees
Rotation: 350 Degrees
Beam Angle: 20 Degrees
Lamp: Non User Replaceable LED
Material: Aluminium/Polycarbonate
Finish: Silver Anodised
Fixing: Magnetic

DL5012Z.WW.10 - 3W Adjustable ZOOM Spotlight (3000K) Black



Diameter: 22mm
Height: 76.3mm
Width: 22mm
Input Voltage: 24VDC
CCT: 3000K
Watts | CRI: 3W | CRI90>
Lumens: 180lm
Tilt: 90 Degrees
Rotation: 350 Degrees
Beam Angle: 10 - 40 Degrees Zoom
Lamp: Non User Replaceable LED
Material: Aluminium/Polycarbonate
Finish: Black Anodised
Fixing: Magnetic

DL5012Z.NW.10 - 3W Adjustable ZOOM Spotlight (4000K) Black



Diameter: 22mm
Height: 76.3mm
Width: 22mm
Input Voltage: 24VDC
CCT: 4000K
Watts | CRI: 3W | CRI90>
Lumens: 180lm
Tilt: 90 Degrees
Rotation: 350 Degrees
Beam Angle: 10 - 40 Degrees Zoom
Lamp: Non User Replaceable LED
Material: Aluminium/Polycarbonate
Finish: Black Anodised
Fixing: Magnetic

MagTrack 24VDC LED Magnetic Track Lighting System

DL5012Z.WW.11 - 3W Adjustable ZOOM Spotlight (3000K) Silver



Diameter: **22mm**
 Height: **76.3mm**
 Width: **22mm**
 Input Voltage: **24VDC**
 CCT: **3000K**
 Watts | CRI: **3W | CRI90>**
 Lumens: **180lm**
 Tilt: **90 Degrees**
 Rotation: **350 Degrees**
 Beam Angle: **10 - 40 Degrees Zoom**
 Lamp: **Non User Replaceable LED**
 Material: **Aluminium/Polycarbonate**
 Finish: **Black Anodised**
 Fixing: **Magnetic**

DL5012Z.NW.11 - 3W Adjustable ZOOM Spotlight (4000K) Silver



Diameter: **22mm**
 Height: **76.3mm**
 Width: **22mm**
 Input Voltage: **24VDC**
 CCT: **4000K**
 Watts | CRI: **3W | CRI90>**
 Lumens: **180lm**
 Tilt: **90 Degrees**
 Rotation: **350 Degrees**
 Beam Angle: **10 - 40 Degrees Zoom**
 Lamp: **Non User Replaceable LED**
 Material: **Aluminium/Polycarbonate**
 Finish: **Black Anodised**
 Fixing: **Magnetic**

DL6023.NW.10 - 4W Adjustable Spotlight (4000K) Black



Diameter: **30mm**
 Height: **60.5mm**
 Width: **22mm**
 Input Voltage: **24VDC**
 Watts | CRI: **4W | CRI90>**
 Lumens: **280lm**
 Tilt: **40 Degrees**
 Rotation: **350 Degrees**
 Beam Angle: **20 Degrees**
 Lamp: **Non User Replaceable LED**
 Material: **Aluminium/Polycarbonate**
 Finish: **Black Anodised**
 Fixing: **Magnetic**

DL6023.NW.11 - 4W Adjustable Spotlight (4000K) Silver



Diameter: **30mm**
 Height: **60.5mm**
 Width: **22mm**
 Input Voltage: **24VDC**
 Watts | CRI: **4W | CRI90>**
 Lumens: **280lm**
 Tilt: **40 Degrees**
 Rotation: **350 Degrees**
 Beam Angle: **20 Degrees**
 Lamp: **Non User Replaceable LED**
 Material: **Aluminium/Polycarbonate**
 Finish: **Silver Anodised**
 Fixing: **Magnetic**

MagTrack 24VDC LED Magnetic Track Lighting System

DL8010.NW.10 - 6W Adjustable ZOOM Spotlight (4000K) Black



Diameter: **55mm**
 Height: **125.2mm**
 Width: **60mm**
 Input Voltage: **24VDC**
 Watts | CRI: **6W | CRI90>**
 Lumens: **480lm**
 Tilt: **90 Degrees**
 Rotation: **350 Degrees**
 Beam Angle: **20 - 60 Degree Zoom Lens**
 Lamp: **Non User Replaceable LED**
 Material: **Aluminium/Polycarbonate**
 Finish: **Black Anodised**
 Fixing: **Magnetic**

DL8010.NW.11 - 6W Adjustable ZOOM Spotlight (4000K) Silver



Diameter: **55mm**
 Height: **125.2mm**
 Width: **60mm**
 Input Voltage: **24VDC**
 Watts | CRI: **6W | CRI90>**
 Lumens: **480lm**
 Tilt: **90 Degrees**
 Rotation: **350 Degrees**
 Beam Angle: **20 - 60 Degree Zoom Lens**
 Lamp: **Non User Replaceable LED**
 Material: **Aluminium/Polycarbonate**
 Finish: **Silver Anodised**
 Fixing: **Magnetic**

