

MINI SERIES Recessed LED Downlights



The simplicity and effectiveness of the innovative MINI SERIES Adjustable LED Downlights is captivating. Available in matt black, matt white, or brushed aluminium in round form. Equipped with a powerful, premium Bridgelux LED in a fixed or tiltable frame. Display Lighting can supply any of the MINI SERIES range of downlights pre-wired with plug & play connectors in sets of 1 - 10 with dimmable or non dimmable drivers.

Features:

- 40 degree lens.
- Three standard finishes available.
- Fixed and Adjustable versions.
- Flush mounting.
- Shallow recessed depth.
- Excellent thermal efficiency.
- 5 year warranty.
- 1W @ 350mA or 2W @ 700mA.

Technical Specifications

Material:	Aluminium
Electrical Connection:	Hard Wired
Power Factor:	92 >
Fixing:	Recessed (2 retaining spring clips)
LEDs:	Bridgelux COB (Integrated Non User Replaceable)
CRI:	90>
Power:	1W @ 350mA 2W @ 700mA
Luminous Efficacy (Lm/W):	100lm/W
Lumens:	100lm @ 350mA 200lm @ 700mA
Beam Angle:	40 Degrees
Class:	III
IP Rating:	IP20
Dimming:	TRIAC 0/1-10V Bluetooth DALI/DALI2
Finishes:	White Black Aluminium
Input Current:	350mA or 700mA Constant Current
Warranty:	5 Years
HS Code:	9405 4099 00
Weight (Nett):	0.08Kg

MINI SERIES Recessed LED Downlights



DL11103B-W-W

Diameter: 52mm
Cutout: 45mm
Height: 36mm
Recessed Depth: 46mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 3000K
Finish: White
Adjustment: 30 Degrees



DL11103B-W-C

Diameter: 52mm
Cutout: 45mm
Height: 36mm
Recessed Depth: 46mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 4000K
Finish: White
Adjustment: 30 Degrees



DL11103B-B-W

Diameter: 52mm
Cutout: 45mm
Height: 36mm
Recessed Depth: 46mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 3000K
Finish: Black
Adjustment: 30 Degrees



DL11103B-B-C

Diameter: 52mm
Cutout: 45mm
Height: 36mm
Recessed Depth: 46mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 4000K
Finish: Black
Adjustment: 30 Degrees

MINI SERIES Recessed LED Downlights

DL11103B-AL-W



Diameter: 52mm
Cutout: 45mm
Height: 36mm
Recessed Depth: 46mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 3000K
Finish: Aluminium
Adjustment: 30 Degrees

DL11103B-AL-C



Diameter: 52mm
Cutout: 45mm
Height: 36mm
Recessed Depth: 46mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 4000K
Finish: Aluminium
Adjustment: 30 Degrees

DL10103B-W-W



Diameter: 42mm
Cutout: 35mm
Height: 35mm
Recessed Depth: 45mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 3000K
Finish: White
Adjustment: Fixed

DL10103B-W-C



Diameter: 42mm
Cutout: 35mm
Height: 35mm
Recessed Depth: 45mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 4000K
Finish: White
Adjustment: Fixed

MINI SERIES Recessed LED Downlights

DL10103B-B-W



Diameter: 42mm
Cutout: 35mm
Height: 35mm
Recessed Depth: 45mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 3000K
Finish: Black
Adjustment: Fixed

DL10103B-B-C



Diameter: 42mm
Cutout: 35mm
Height: 35mm
Recessed Depth: 45mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 4000K
Finish: Black
Adjustment: Fixed

DL10103B-AL-W



Diameter: 42mm
Cutout: 35mm
Height: 35mm
Recessed Depth: 45mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 3000K
Finish: Aluminium
Adjustment: Fixed

DL10103B-AL-C



Diameter: 42mm
Cutout: 35mm
Height: 35mm
Recessed Depth: 45mm
Watts: 1W @ 350mA | 2W @ 700mA
Lumens: 100lm @ 350mA | 200lm @ 700mA
Luminous Efficacy: 100lm/W
CCT: 4000K
Finish: Aluminium
Adjustment: Fixed

MINI SERIES Recessed LED Downlights

POWER & DIMMING OPTIONS

P&P/BT: Plug & Play -  **Bluetooth** Controllable Driver (*no mains lead*)

[Casambi App available for IOS on App Store & Android on Google Play Store](#)

P&P/DA: Plug & Play - 1-10V Dimmable Driver (*no mains lead*)

P&P/DD: Plug & Play -  **DALI** Dimmable Driver (*no mains lead*)

P&P/DT: Plug & Play - Mains (TRIAC) Dimmable Driver (*no mains lead*)

P&P/OO: Plug & Play - On/Off Driver (*no mains lead*)

MODEL	POWER/DIMMING
DL11103B-W-W	P&P/BT
DL11103B-W-C	P&P/DA
DL11103B-B-W	P&P/DD
DL11103B-B-C	P&P/DT
DL11103B-AL-W	P&P/OO
DL11103B-AL-C	
DL10103B-W-W	
DL10103B-W-C	
DL10103B-B-W	
DL10103B-B-C	
DL10103B-AL-W	
DL10103B-AL-C	

