

V-TRACK Modular Vertical Track Spotlights



V-TRACK is a 24VDC modular vertical track lighting system designed for installing into retail and museum displays to give discrete flexible illumination to high end products and artefacts. The vertical track of the V-TRACK track system can be installed vertically up to 1100mm and can utilise three different types of LED light sources that simply clip into the TRACK at any height giving the end user the ability to change the lighting configuration at any time using:


- 5 lengths of linear LED strip modules.
- Single, double and triple adjustable focused spotlight modules.
- Available in high quality Black or Silver anodised finishes.
- Available with 3000K or 4000K LEDs.

Technical Specifications

Height:	< 1100mm (<i>visible height</i>)
Material/s:	Aluminium
Electrical Connection:	Plug & Play Hard Wired (<i>2500mm tails as standard, can be specified</i>)
CCT:	WW - 3000K NW - 4000K
Fixings:	Rear Fixing
CRI Rating:	CR190>
Class:	III
IP Rating:	IP20
Finishes:	10 - Black 11 - Silver
Track Width:	12.5mm
Track Depth:	10.5mm
Input Voltage:	24VDC (<i>constant voltage</i>)
Warranty:	5 Years
Ordering:	7 step order code (<i>see page 3</i>)
Dimming:	Not Dimmable



V-TRACK Modular Vertical Track Luminaires



Length: L1100mm (*Can be Cut to Size*)
Height: 10.5mm
Width: 12.5mm
Finishes: Black | Silver
Voltage: 24VDC



L - LED Linear Strip Modules

Length/s: L150 - 150mm (*140lm*)
 L300 - 300mm (*290lm*)
 L600 - 600mm (*570lm*)
 L900 - 900mm (*860lm*)
 L1049 - 1049mm (*1000lm*)
CCT: 3000K | 4000K (CRI90>)
Beam Angle: 100 Degrees



S1 - LED Spotlight Modules

Length: 50mm
Watts: 1.4W (*60lm*)
Finishes: Black | Silver
CCT: 3000K | 4000K (CRI90>)
Beam Angle: 20 Degrees



S2 - LED Spotlight Modules

Length: 100mm
Watts: 2 x 1.4W (*140lm*)
Finishes: Black | Silver
CCT: 3000K | 4000K (CRI90>)
Beam Angle: 20 Degrees



S3 - LED Spotlight Modules

Length: 150mm
Watts: 3 x 1.4W (*230lm*)
Finishes: Black | Silver
CCT: 3000K | 4000K (CRI90>)
Beam Angle: 20 Degrees



RF - V-TRACK Rear Fixing Base

Collar Diameter: 23mm
Cutout Diameter: 20mm
Finishes: Black | Silver
Thread Length: 40mm
Panel Thickness: 30mm (*Maximum*)



LE - V-TRACK Live Feed

Finishes: Black | Silver
Cable Length: 2500mm

V-TRACK Ordering

POWER & DIMMING OPTIONS

P&P Plug & Play - Standard On/Off Driver (2m mains lead & UK plug)

P&P/OO: Plug & Play - Standard On/Off Driver (no mains lead)

SEVEN STEP ORDERING

	1	2	3	4	5	6	7
MODEL	HEIGHT	LED MODULES	No of MODULES	CCT	FIXING	FINISH	POWER
V-TRACK	< 1100mm (Visible Height)	S1 S2 S3 L150 L300 L600 L900 L1049	X1 X2 X3 X4 X5 X6 X7 X8 X9 X10	WW NW	RF	10 11	P&P P&P/OO

Example Order Code: V-TRACK.500.S1X4.NW.RF.10.P&P/OO

NOTES:

V-TRACK Installation

