

S1052 - Spectrum Miniature LED Pro Spotlight



S1052 luminaire is supplied complete with a stirrup bracket that can be screwed or riveted to most types of surfaces. It is ideal for screwing to the uprights in showcases and the cable can be fed up or down to the driver. This fitting stands only 50mm high and is perfect for applications that require miniature lighting.

- Integrated LED.
- Specialised focused lighting for museum and retail showcases.
- Low heat illumination.
- No ultraviolet light so does not fade materials.
- Unobtrusive.
- Bespoke product manufactured to your specification.
- Reduces heat emissions and heat build-up in store.
- Reduces energy bills by up to 80%.
- Dimmable

Technical Specifications

Head Diameter:	25mm
Material/s:	Brass
Electrical Connection:	Plug & Play Hard Wired (1000mm tails as standard)
CCT (Lumens):	VW - 3000K (142lm) NW - 4000K (161lm) CW - 5000K (161lm)
Watts:	1W (integrated non-user replaceable LED)
UV:	0.2 microwatts/m2
Fixings:	Screwfix Bracket
CRI Rating:	CRI90>
Class:	III
IP Rating:	IP20
Protection Class:	IK02
Finishes:	01 - White 02 - Black 03 - Chrome 04 - Polished Brass 05 - Brushed Chrome 06 - Antique Brass 07 - Polished Nickel 08 - Brushed Nickel 15 - Brushed Brass 16 - Rose Gold XXX - RAL Colours
Input Voltage:	350mA
Forward Voltage (Vf):	3V
Beam Angles:	10 25 40 60 Degrees
Warranty:	5 Years
Dimming:	ON/OFF 1-10V TRIAC DALI DMX Bluetooth (Casambi)
Ordering:	5 step order code (see page 3)



POWER & DIMMING OPTIONS

- P&P** Plug & Play - Standard On/Off Driver (*2m mains lead & UK plug*)
- P&P/BT:** Plug & Play -  **Bluetooth** Controllable Driver (*no mains lead*)
Casambi App available for IOS on App Store & Android on Google Play Store
- P&P/DA:** Plug & Play - 1-10V Dimmable Driver (*no mains lead*)
- P&P/DAP:** Plug & Play - 1-10V Dimmable Driver with Pot Dimmer (*2m mains lead & UK plug*)
- P&P/DD:** Plug & Play - DALI Dimmable Driver (*no mains lead*)
- P&P/DT:** Plug & Play - Mains (TRIAC) Dimmable Driver (*no mains lead*)
- P&P/OO:** Plug & Play - Standard On/Off Driver (*no mains lead*)

FIVE STEP ORDERING

	1	2	3	4	5
MODEL	CCT	BEAM ANGLE	FINISH	SPOTS PER SET	POWER
S1052	WW	10	01	X1	P&P
	NW	25	02	X2	P&P/BT
	CW	40	03	X3	P&P/DA
		60	04	X4	P&P/DAP
			05	X5	P&P/DD
			06	X6	P&P/DT
			07	X7	P&P/OO
			08	X8	
			15	X9	
			16	X10	
			XXX (RAL)		

Example Order Code: **S1052.WW.40.02.X2.P&P/OO**

NOTES: